



BOS-DRAW 2235

SYNTHETIC DRAW & STAMP COMPOUND

Description:

Bos-Draw 2235 is an amber, semi-paste product in its concentrated (state) condition. It contains the finest synthetic soaps, corrosion inhibitors and extreme pressure (EP) additives, to assure optimum performance in a wide variety of drawing applications.

Uses:

Bos-Draw 2235 has been developed as a heavy duty, versatile product that can be used on both ferrous and non-ferrous metals. It can be used effectively in both shallow and deep drawing operations as well as other applications, including bending, stamping, blanking, etc. Provides exceptional resistance to galling, seizing, scratching and scuffing.

Method of Application:

Dilute Bos-Draw 2235 drawing and forming lubricant with water to desired consistency and concentration according to the requirements and severity of the job.

Advantages:

- Pleasant odor
- High film strength & E.P. properties to prevent galling
- Mixes easily
- Excellent load carrying characteristics
- Non-irritating to normal skin
- Good versatility on a large variety of jobs & metals
- Stable in concentrated form
- Germicidal additives to eliminate rancidity

Typical Properties:

Color:	Amber
Solubility:	Water
Pounds per gallon:	8.4
Specific Gravity:	1.01
pH:	9.0

Bosse Lubricants®
800-367-9966 www.metalfluids.com

The product information and specifications contained herein have been compiled for the convenience of the user. It is intended to be used by people with technical skills. Bosse Lubricants & Star Metal Fluids LLC disclaims any warranty, expressed or implied, of merchantability for any specific use, especially when such use is beyond our control. Whenever the information herein is to be used for a critical application it is the responsibility of the user to verify independently the appropriateness of its use in his application. This information is not intended as a license to operate under, or a recommendation to infringe any Bosse Lubricants patent.