

DASCO® VANISHING OIL 678

DESCRIPTION

Dasco Vanishing Oil 678 is a medium-duty lubricant designed for those applications wherein no oil film is permissible. **Dasco Vanishing Oil 678** films will evaporate leaving no oil film that will inhibit further processing.

Dasco Vanishing Oil 678 should be used as received and can be applied by spraying, dipping, brushing or roller coating methods.

SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT (SCAQMD, RULE 1144):

THIS PRODUCT CANNOT BE USED IN THE SCAQMD

FEATURES/ BENEFITS

- Odorless carrier solvent evaporates readily leaving a minimum residue so no cleaning is necessary after part is stamped.
- Enhanced lubrication package to reduce metal pickup and galling for improved tool and die life.

CAUTION

Product contains solvent.

Use mechanical ventilation and guard against open flames or other ignition sources.

DATA (TYPICAL VALUES)

Appearance	Clear liquid
Flash Point, Closed Cup	133°F (56°C)

HEALTH AND SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

CF 14.02 US



Houghton International Inc.
 Madison and Van Buren Aves.
 P. O. Box 930
 Valley Forge, PA 19482-0930

Phone: 610-666-4000
 Fax: 610-666-0174
 info@houghtonintl.com
 www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.