

# XTREME KUT 737

## High Performance Straight Oil

### Performance Benefits

- High stock removal in demanding operations provided by superior lubrication
- Dramatic increase in tool life due to unique combination of boundary and extreme pressure additives
- Good wetting, cooling, and fine settling characteristics due to low viscosity
- Safe for use on all metals

XTREME KUT 737 is a high performance cutting and grinding oil designed for rigorous metal removal operations. XTREME KUT 737 contains extreme pressure lubricity additives that extend tool life and provide excellent surface finishes in the most severe applications. XTREME KUT 737 utilizes state of the art polar lubricants that enhance performance at the point of cut while providing superior oxidation stability for long service life, fewer rejects and increased productivity. XTREME KUT 737 is safe for use on both ferrous and non-ferrous metals.

### Operations

Drilling	Boring	Grinding
Tapping	Turning	Milling

### Typical Characteristics

Appearance.....	Clear, yellow liquid
Copper Corrosion ASTM 130.....	1B
Density .....	7.26 lbs./gal
Flash Point, COC.....	328°F (164°C)
Viscosity, SUS @ 100°F (38°C).....	65
Fat.....	Yes
Chlorine.....	Yes
Sulfur.....	Yes
Active sulfur.....	No
Phosphorus.....	Yes

### Packaging

XTREME KUT 737 is packaged in 310-gallon, one-way tote tanks and 55-gallon, non-returnable steel drums. Bulk and 5-gallon pails are also available.

**QUALICHEM**  
Metalworking Fluids

AN ISO 9001:2008 COMPANY  
2003 Salem Industrial Drive | Salem, VA 24153  
540.375.6700  
[www.qualichem.com/metalworking](http://www.qualichem.com/metalworking)