

Technical Data Sheet

CleanSafe™ 585

Product Description

CleanSafe 585 Aqueous Cleaner is a high performance cleaning agent specially designed for use in ultrasonic equipment. It effectively removes a wide range of soils including drawing oils, coolants, stamping oils and other metalworking fluids. CleanSafe 585 effectively removes particulate matter from components with complex geometries. Formulated with exceptional levels of corrosion inhibitors, CleanSafe 585 is suitable for use on ferrous and non-ferrous alloys as well as plastic parts.

Features and Benefits

- VOC free
- NPE/APE free
- Phosphate free
- Corrosion Inhibition

- Material Compatibility
- Oil Splitting
- Long Bath Life

Properties

Odor Mild
Flash Point None
Specific Gravity (25 °C) 1.08
pH Value (10%) 11.2

Cloud Point >200 °F (93 °C)

Equipment

Specially designed to operate in ultrasonic cleaning equipment.

Process

Wash Bath Concentration 2-10%

Wash Bath Temperature 70-180 °F (21-82 °C) DI Water Rinse Temperature 70-180 °F (21-82 °C)

Environmental/Regulatory

Ozone Depletion Potential (ODP)

Global Warming Potential (GWP)

Chemical Oxygen Demand (COD) (0.1% conc.)

Volatile Organic Compound (VOC)

Hazardous Air Pollutant (HAP)

Zero

288 mg/L

0 g/L

Superfund Amendments and Reauthorization Act (SARA)

Hazardous Air Pollutants (NESHAPs)

Resource Conservation and Recovery Act (RCRA)

Not Regulated

Not Regulated

Nonylphenol Ethoxylates (NPEs)

Alkylphenol Ethoxylates (APEs)

Phosphates

None



Technical Data Sheet

CleanSafe™ 585

Disposal/Safety

Disposal

Vantage recommends contacting your current or local environmental service company for proper disposal. Safety

Please see Safety Data Sheet for further information.

Packaging

Available in 45 lb (20 kg) pails and 495 lb (225 kg) drums.

Shelf Life

36 months when stored in original, sealed container above 50 °F (10 °C). Protect product from freezing.



ISO 9001:2008







CleanSafe is a trademark of Vantage Specialties, Inc.

Typical property data is not intended for specification purposes. Vantage Specialties, Inc., its sales agents and distributors make no warranty of merchantability of the product or of product fitness for any particular purpose. This product and all information supplied are used at the purchaser's own risk. The purchaser assumes all risk of use or handling of the product, whether in accordance with directions or not.